



THE ENTERPRISE CENTRE, BALLYCORUS, KILTERNAN, DUBLIN 18. TEL: 01-2822877/2822496 FAX: 01-2822653 e-mail: info@mcc.ie

REVISION NO: 1
ORIGINAL ISSUE: 14.07.09
THIS ISSUE: 14.07.09
ISSUED BY: H McConnell

TECHNICAL DATA SHEET **2722 ISOTAC THINNERS**

2722 Isotac Thinners is a particular blend of solvents designed for thinning our Isotac Airport Runway Paint. (Please also refer to our Material Safety Data Sheet.)

General Properties

Solvent	Mixture of Aromatic Hydrocarbons and a Ketone.
Specific Gravity	0.845 – 0.855 @ 15.6°C
Flammability	Highly flammable solvent giving off highly flammable heavy vapour. Flash point: minus 2 °C.
Toxicity	Under conditions of good ventilation toxic limits should not normally be exceeded. Threshold Limit Value 50 ppm.
Handling Precautions	Isolate from sources of heat, naked flames and sparks. Maintain efficient ventilation. Avoid excessive inhalation of vapour. Avoid contact with skin and eyes.
Spillage	Prevent spread with sand or earth. Absorb the spillage with sand, earth or other inert absorbent and dispose of as highly flammable waste.
Storage Life	12 months at 5 - 25 °C

The information given above is issued as a guide to the use of our products and every effort is made to ensure that it is accurate and in accordance with latest technical developments. We cannot accept responsibility for results, as we have no control over the conditions under which our products are used. Further advice and technical service is available from our trained sales and laboratory staff.