McConnells Datasheet
Revision 2
Issued: 09-10-2008

FORTAGUARD Q777 Anti- Climb Paint

Q777 is a non-drying, non- oxidising thick coating used to deter unauthorised access.

McConnells **FORTAGUARD Q777** Anti-Climb paint will assist in the secure protection of property and may be applied to wall cappings, windowsills, downpipes etc... **FORTAGUARD Q777** can be applied by an individual with DIY painting experience with due care and attention.

- Protects as a thick, slippery coating.
- Access is restricted.
- Very high in solids.
- Non- drying. Waterproof and water vapour permeable.
- Four colour choices.

Black	Grey	Tile Red	Green

Packing
Supplied in 4kgs containers.

Preparation of surfaces
New concrete should be allowed to dry for one month before coating. Surfaces to be coated should be clean, dry, and free of dust, dirt, grease, waxes, efflorescence, laitance and any loose material

Pre-application procedure.
Before application, seal any porous surfaces with **Fortacryl Q641 Sealer,** abrade and prime smooth surfaces such as pre painted areas.

Application
Apply in dry conditions preferably by an old stiff brush while wearing goggles and appropriate protection to skin.

Touch dry: N/A
Recoatable: N/A
Fully hard: N/A
(Not recommended for use where the temperatures exceeds 35ºC).

Coverage
Coverage is approximately $2m^2$ per litre per coat depending on surface porosity. Apply sufficient Q777 to inhibit gripping.

Important Information
Use only in well-ventilated areas. Protect containers and contents from excessive heat.

Storage/Shelf Life
At least 24 months in correctly resealed container, in a cool, dry and frost-free location. Protect from frost.

Cleaning Tools and Equipment
Always remove as much **FORTAGUARD Q777** as possible from the application equipment before washing. Do not empty **FORTAGUARD Q777** into drains or water courses. Equipment may be cleaned with our **FORTACLEAN Synthetic** Thinners. Empty containers are non-hazardous, but should be disposed of in accordance with local and national regulations. Most local authorities have facilities for disposal of paint waste and used paint tins.
FORTAGUARD Q777 is classed as hazardous for supply or for transport.
VOC content is less than 100gms/kg.
Flash Point is above 32 ºC.

Ordering
All of our products are available direct from McConnells and are sold subject to the Company's Standard Conditions of Sale.

The Company and its employees are often asked on potential uses of McConnell's products in addition to those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by McConnells. The Customer/User must always test our product in their particular application to satisfy themselves that their requirement is fulfilled before proceeding with their project.

Supplied by

McConnells COATINGS ADHESIVES

International Coatings Limited
The Enterprise Centre, Ballycorus,
Kilternan, Dublin 18.
Tel: 01 2822877 Fax: 01 2822653